

## PCA EXCEL one4all for fluorescent lamps

- Digital dimmable ballast for fluorescent lamps with one4all interface, controlable with digital DALI- or DSI-signals or manually controlable via standard push to make switches without any need of luminaire rewiring.
  - Automatic detection of the connected control signal.
  - Integrated SMART interface for ambient light regulated applications
  - Polarity free digital Interface
  - Single addressability in DALI mode
  - Manual control (switchDIM) via standard push to make switches. Memory function for the last operation mode in case of mains failures. E.g. standby mode
  - Programmed warm start without any light flash
  - Flicker free dimming operation light level independent and through the complete temperature range
  - Adjustable DC-emergency light level between 70% and 1% (optimised power consumption for centralised battery systems)
  - Powerless switching through the digital interface (no switching via mains necessary)
  - ON/OFF and dimming commands can be given through the same control wires
- 
- Status feedback (lamp- and ballast-status)
  - Internal storage of up to 16 light presets, 16 group assignments and one individual address
  - Individual adjustable fade times for scene changes and manual dimming.
  - At the maximum allowed temperature a nominal life time of 50.000h with a nominal failure rate of 0,2% per 1000h can be expected
  - Logarithmic dimming curve that is optimised according to the sensitivity to the eye
  - Safe shutdown of defective lamps (e.g. rectifying effect)
  - Automatic restart after lamp replacement
  - CELMA energy classification EEI=A1
  - Constant light output independent of fluctuating supply voltage
  - Suitable for emergency applications according to VDE 0108
  - Approvals:  
ENEC 11, CE, EEI=A1  
(EN 55015, EN 55022, EN 60929, EN 61000-3-2, EN 61347-2-3, EN 61547, installations according to VDE 0108)
  - Product designation:  
PCA x/yy XX EXCEL one4all  
XX...lamp type  
e.g. PCA 1/14 T5 EXCEL one4all  
PCA 1/26 TCT EXCEL one4all  
PCA 1/55 T5c EXCEL one4all