

Product / function matrix



Benefits	Product characteristics	TE speedy	TE VIPER
High functionality	Wattage range	20 – 105 VA	20 – 105 VA
	SELV	•	•
	Mains voltage	230 – 240 V 50/60 Hz	230 – 240 V 50/60 Hz
	For use in emergency lighting systems (EN 50172)		
	Soft start	•	•
	Constant output voltage		
High level of safety	Intelligent Voltage Guard for constantly checking the mains voltage		
	Short-circuit shutdown feature with automatic restart	•	•
	Overtemperature protection	•	•
	Overload protection	•	•
	Protection class	II	II
	Type of protection	IP20	IP20
Efficient dimming	Leading-edge and trailing-edge phase dimmers	•	•
	switchDIM		
	corridorFUNCTION		
	Digital interface DSI / DALI		
High degree of flexibility	Built-in version		
	Surface-mounted version	•	•
	Double-sided terminals		•
	Single-sided terminals	•	
High quality	Approval marks		
	Guarantee	5 years	3 years



TE BASIC	TE 0105	TE one4all sc	TE one4all cc	TE-DC 2 one4all
20 – 60 VA	35 – 105 VA	20 – 150 VA	20 – 105 VA	100 – 300 VA
•	•	•	•	•
220 – 240 V 50/60 Hz	230 – 240 V 0/50/60 Hz	230 – 240 V 0/50/60 Hz	230 – 240 V 0/50/60 Hz	230 – 240 V 0/50/60 Hz
		•	•	•
	•	•	•	•
	•	•	•	•
•	•	•	•	•
	•	•	•	•
•	•	•	•	•
II	II	II	II	II
IP20	IP20	IP20	IP20	IP20
•	•			
		•	•	•
		•	•	•
		•	•	•
•				
	•	•	•	•
	•	•	•	•
•				
3 years	5 years	5 years	5 years	5 years