

Controls and Connectivity

Application controllers supporting MSensor G3 family



TRIDONIC

Tridonic MSensor G3 family sensors are developed according to DALI Standard EN 62386-101 Ed.2, also known as DALI 2. To be able to use the sensor in such installation, an application controller is necessary.

The following application controllers were tested to work in combination with the Tridonic MSensor G3 family:

| Manufacturer | Product name |
|--------------|---|
| LOYTEC | L-DALI Controller |
| BECKHOFF | KL6821 DALI/DALI 2 multi-master and power supply terminal |
| WAGO | DALI Multi-Master 753-647 WAGO-I/O-SYSTEM 750/753 |
| ES SYSTEM | VERTEX – DALI CONTROL UNIT |

The MSensor G3 family consists of different multi-sensors for DALI systems:

MSensor G3 SFI 30 PIR 16DPI WH NEW



MSensor G3 SFI 30 PIR 10DPI WH NEW



MSensor G3 SFI 30 PIR 5DPI WH/BK



More information about the new DALI Standard EN 62386-101 Ed.2 also known as DALI 2 and the difference between DALI and DALI-2 can be found in a separate the document "Comparison between DALI & DALI-2" at

https://www.tridonic.com/com/en/download/technical/DALI-Comparison-between-DALI-and-DALI-2_en.pdf.

If you have any additional question please contact your local Tridonic contact.